## Amendment to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

## **Listing of Claims:**

- 1. (Cancelled).
- 2. (Cancelled).
- 3. (Currently amended) An extrusion head in accordance with claim 2 An extrusion head for continuous extrusion of molten polymer in a predetermined cross-sectional shape, the molten polymer being supplied from a source, the cross-sectional shape including at least one lumen, the head comprising:
  - a) an extrusion tip having an outer surface;
- b) an extrusion die surrounding said tip and having an inner surface cooperating with said tip surface to define a flow channel therebetween, said flow channel defining a direction of flow of said molten polymer in said head;
- c) at least one lumen pipe assembly extending through a wall of said die into said flow channel, said pipe assembly having a first portion extending transversely of said flow direction and a second portion extending parallel to said flow direction, said first and second pipe portions being joined at a right angle;

157597.1 Page 2 of 7

- d) means for adjusting the radial position of said lumen pipe assembly in said flow channel, wherein said means for adjusting includes a pin vise mounted in said wall of said die.
- 4. (Currently amended) An extrusion head in accordance with elaim 2 An extrusion head for continuous extrusion of molten polymer in a predetermined cross-sectional shape, the molten polymer being supplied from a source, the cross-sectional shape including at least one lumen, the head comprising:
  - a) an extrusion tip having an outer surface;
- b) an extrusion die surrounding said tip and having an inner surface
  cooperating with said tip surface to define a flow channel therebetween, said flow
  channel defining a direction of flow of said molten polymer in said head;
- c) at least one lumen pipe assembly extending through a wall of said die into said flow channel, said pipe assembly having a first portion extending transversely of said flow direction and a second portion extending parallel to said flow direction, said first and second pipe portions being joined at a right angle;
- d) means for adjusting the radial position of said lumen pipe assembly in said flow channel, wherein said means for adjusting includes a removable gauge block.

Claims 5-16 (Cancelled).

- 17. (Currently amended) An extrusion head in accordance with elaim 16 An extrusion head for continuous extrusion of molten polymer in a predetermined cross-sectional shape, the molten polymer being supplied from a source, the cross-sectional shape including a plurality of lumens, the head comprising:
  - a) an extrusion tip having an outer surface;
- b) an extrusion die surrounding said tip and having an inner surface
  cooperating with said tip surface to define a flow channel therebetween, said flow
  channel defining a direction of flow of said molten polymer in said head, wherein
  said extrusion die includes first and second parts joinable along mating surfaces
  thereof;
- c) a distribution manifold formed in at least one of said first and second die parts and including a plurality of runners;
- d) a lumen pipe assembly extending from each of said runners into said
  flow channel and being clamped between said mating surfaces, each one of said
  pipe assemblies having a first portion extending transversely of said flow
  direction from said runner and a second portion extending parallel to said flow
  direction, said first and second pipe portions being joined at a right angle; and
- e) means for adjusting the radial position of said lumen pipe assemblies in said flow channel, wherein said means for adjusting includes a removable gauge block.